

COMFORT IS AVAILABLE TO EVERYONE



NOVatec STANDARD water heaters



wetheater
2000W



2-year
warranty



Service
Quick Solution



Quality and
reliability



NOVA tec –
Your smart choice
without overpaying!



**NOVAtec — One of the leading manufacturers of water heaters.
We were created to make comfort accessible to everyone.**

Since 2001, we have been manufacturing water heaters that last for years.

**We have 24 years of reliable operation behind us—a choice proven over time.
Millions of satisfied families who choose and recommend
NOVAtec time and time again.**





Seria **STANDARD**

Simple and reliable



Hidden temperature
controller



Heater
2 kW



Magnesium anode
For additional corrosion
protection

Classic, vertical water heaters with a heating element, a dial thermometer, and a light indicator. The water heaters are protected against overheating and dry heating.



S 100L

Power:	2000 W
Heating time:	195 min od 15°C do 65°C
Protection rating:	IP44
Voltage:	230 V
Rated pressure:	0,6 MPa
Dimensions:	93 × 46 × 46 cm



S 80L

Power:	2000 W
Heating time:	155 min od 15°C do 65°C
Protection rating:	IP44
Voltage:	230 V
Rated pressure:	0,6 MPa
Dimensions:	75 × 46 × 46 cm



S 50L

Power:	2000 W
Heating time:	97 min od 15°C do 65°C
Protection rating:	IP44
Voltage:	230 V
Rated pressure:	0,6 MPa
Dimensions:	67 × 46 × 46 cm

Seria **STANDARD PLUS** ✨



Top quality materials



External temperature
controller



Heater
2 kW



Foam thickness
25 mm

Standard Plus series water heaters are equipped with an external temperature controller located on the bottom cover of the unit, allowing easy setting of the desired water heating temperature. These units feature a 2 kW heating element and improved thermal insulation, ensuring high efficiency and comfort of use.



SP 100L

Power:	2000 W
Heating time:	195 min od 15°C do 65°C
Protection rating:	IP44
Voltage:	230 V
Rated pressure:	0,6 MPa
Dimensions:	91 × 46 × 46 cm



SP 80L

Power:	2000 W
Heating time:	155 min od 15°C do 65°C
Protection rating:	IP44
Voltage:	230 V
Rated pressure:	0,6 MPa
Dimensions:	76 × 46 × 46 cm



SP 50L

Power:	2000 W
Heating time:	97 min od 15°C do 65°C
Protection rating:	IP44
Voltage:	230 V
Rated pressure:	0,6 MPa
Dimensions:	58 × 46 × 46 cm



SP 35L

Power:	2000 W
Heating time:	68 min od 15°C do 65°C
Protection rating:	IP44
Voltage:	230 V
Rated pressure:	0,6 MPa
Dimensions:	44 × 46 × 46 cm


Seria UNIVERSAL

Horizontal and vertical installation



A water heater that adapts to your needs

Horizontal installation
— perfect for alcoves,
cabinets, or ceilings



External
temperature controller



Heater
2 kW



Foam thickness
25 mm

Special design
of the heating element
ensures efficient
heating

For those looking for a flexible solution for heating water, the PREMIUM UNIVERSAL is a water heater that combines simple horizontal and vertical installation, easy temperature control, and a durable tank.

Convenient installation —
thoughtful design, quick setup
without unnecessary complications.



U 100L

Power:	2000 W
Heating time:	195 min od 15°C do 65°C
Protection rating:	IP44
Voltage:	230 V
Rated pressure	0,6 MPa
Dimensions:	93 × 46 × 46 cm

U 80L



Power:	2000 W
Heating time:	155 min od 15°C do 65°C
Protection rating:	IP44
Voltage:	230 V
Rated pressure	0,6 MPa
Dimensions:	75 × 46 × 46 cm

U 50L




Power:	2000 W
Heating time:	97 min od 15°C do 65°C
Stopień ochrony:	IP44
Voltage:	230 V
Rated pressure	0,6 MPa
Dimensions	67 × 46 × 46 cm

Seria **COMBI**



With left
or right
connection

Kombinowana metoda podgrzewania wody



Heat exchanger
surface area: 0.5 m²



Grzałka
2 kW



External
temperature controller

Versatile, convenient to use, and highly efficient. Be as independent and autonomous as possible with NOVAtec. Water heaters can heat water using either an electric heating element or a heat exchanger.

External heat sources include solar collectors and boilers.



CB 100L

Power:	2000 W
Heating time:	195 min od 15°C do 65°C
Stopień ochrony:	IP44
Voltage:	230 V
Rated pressure	0,6 MPa
Dimensions	91 × 46 × 46 cm



CB 80L

Power:	2000 W
Heating time:	155 min od 15°C do 65°C
Stopień ochrony:	IP44
Voltage:	230 V
Rated pressure	0,6 MPa
Dimensions	76 × 46 × 46 cm

More detailed information can be found on our website.





+48 606 346 811

Serwis / Biuro

serwis.novatec@gmail.com



novatec-heat.com